

## 5MP Outdoor IR Fix focal Bullet Camera

# Model: IC-SWA71F

- Easy installation with NVR
  - 5.0 MP (2592\*1944) Resolution
  - Fix-Focal 3.6mm 6.0 Megapixel
  - Supports ONVIF
  - WDR Function
  - PoE
  - Motion Detection
  - H.265/H.264 Supports
- Day&Night (ICR)  
IR LED: 35m(42Unit)  
3-axis mechanical design for installation



### SPECIFICATIONS

VIDEO	
Image Sensor	1/2.9", 5 megapixel progressive scan Sensor
Max. Resolution	2592*1944
Scanning Mode	Progressive Scan
Lens type	FIX-FOCAL
Focal Length	3.6mm 6.0 Megapixel IR lens
Aperture	F.2.1
Iris Control	Electronic Iris
Min. Illumination	COLOR : 0.1 lux F1.3 B/W: 0 lux (IR LED ON)
S/N Ratio	31.2dB
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/8000), Anti-Flicker, Slow Shutter(1/7.5,1/15)
Day & Night	IR cut filter with auto switch
IR Distance (LEDs)	35m (42Unit)
Image Setting	Configurable Exposure, White Balance, Sharpness
Digital Noise Reduction	Configurable 2DNR-3DNR
Backlight Compensation	On / Off / HSBLC
Mirroring / Pivot	Horizontal / Vertical / Pivot
Image Stabilizer	Yes
Privacy Masking	16 Zones
Intelligent Video	Video Motion Detection
NETWORK	
Supported Resolution	2592*1944 , 2560 x1960 , 1920x1080, 1280x720 , 704x480
Multi-Video Streaming	Triple streaming
Network Protocols	10/100M adaptive, 8KV antistatic capability; RTSP/HTTP/SMTP/FTP/DHCP/NTP/QQIOT/RT
thernet	RJ45(10/100BASE-T)
ALARM & EVENT	
Trigger Event	Motion Detection
Event Buffering (Pre & Post)	Yes
Event Notification	Remote S/W, Email (with Image)
ENVIRONMENTAL	
Out-door Ready	IP66
Operating Temperature	-10°C ~ +50°C (+14°F ~ +122°F) *Starting up at above 0°C (32°F)
Operating Humidity	0% ~ 90%
ELECTRICAL	
Power Source	12VDC, PoE(48V-DC)
Power Consumption	6.2W
Approvals	FCC, CE, UL
MECHANICAL	
Dimensions (W x H x D)	100x81x245
Weight	440 g

### DIMENSIONS

(unit-mm)

