

## SMART NVR 36Channel 4K Recorder

# NV836S



- Up to 300M Bandwidth 4K real-time recording
- P2P cloud service, including cloud connecting, cloud monitoring
- Easy to install, set-up with cameras
- 36 Channel 4K camera support
- up to 24TB (4 HDD)
- Support 15X zoom under preview and playback modes
- Supports cameras ONVIF , i9 , Slink , RTSP
- H.265/H.264



### SPECIFICATIONS

VIDEO	
Video Inputs	36x(3840*2160)+sub[960*576] H.265 8M/ch 36ch 4K IP Camera
Supported Camera	ONVIF , i9 , Slink , RTSP
Video Outputs	1 HDMI, 1 VGA
Display Resolution	4K / 5MP / 3MP / 1080P / 960P / 720P
Digital Zoom	x2 ~ x15
RECORDING	
Recording Resolution	Up to 4K (Depending on IP Camera)
Compression	H.264/H.265
Recording Mode	Support manual , auto, dynamic detection, alarm trigger record mode
Trigger Events	Motion detection, Video loss
PLAYBACK	
Performance	4ch 4K playback/9ch 5MP playback/16ch 1080 playback
Search Modes	Time-lapse, Event log, Thumbnail, Motion, Text-in
Digital Zoom	x2 ~ x15
STORAGE & Backup	
HDD	Support 4xHDD Sata (Up to 10TB capacity for each disk)
Backup mode	Network backup,USB hard disk, Usb burner,SATA burner
Data Export Device	USB HDD, USB Stick
NETWORK	
NetworkPort	1 RJ45,10M/100M/1000M self-adaptive LAN port
Video in Connection	Ethernet(IP Camera)
Remote Data Export	AVI, i8
Event Notification	Email (attach clip (.cbf) .MP4), Callback to Remote S/W Push notification (Mobile), SNS (Twitter)
Two-way audio	Yes
Client Viewer	General VMS software
INTERFACE	
Action with Alarm	Support
Audio compression	G.711A
User Interface	Mouse
GENERAL	
Operating System	Embedded Linux
System Resources	Simultaneous multi-channelreal-time recording,playback,network operation, USB backup
PTZ control	Control PTZ device by network
ONVIF	Support
Approvals	FCC, CE
Power Supply	12V/8A
Power Consumption	<25W(without HDD)
Dimension	350mm(W)x240mm(D) 68mm(H)

### DIMENSIONS

