

NV8XP48



- Up to 80M Bandwidth 4K real-time recording
- Support P2P Connection
- Easy to install, set-up with cameras
- 8 Channel POE Up to 4K camera
- up to 20TB (2 HDD)
- Support 15X zoom under preview and playback modes
- Supports cameras ONVIF , i9 , Slink , RTSP
- H.265/H.264



SPECIFICATIONS

VIDEO	
Video Inputs	8ch POE network compressed video input (compatible with 4K with 4K resolution)
Supported Camera	ONVIF , i9 , Slink , RTSP
Video Outputs	1ch HDMI Resolution: 3840×2160/30Hz,1920×1080/60Hz
Display Resolution	4K/5M/3M/1080P/720P
Digital Zoom	x2 ~ x15
RECORDING	
Recording Resolution	Up to 4K (Depending on IP Camera)
Compression	H.264/H.265
Recording Mode	Time-Lapse, Manual, moving detection,Event , alarm, dynamic test
Trigger Events	Motion detection, Video loss
PLAYBACK	
Performance	1ch 4K, 4ch 1080P Playback
Search Modes	Time-lapse, Event log, Thumbnail, Motion, Text-in
Digital Zoom	x2 ~ x15
STORAGE & Backup	
HDD	Support 2xHDD Sata (Up to 10TB capacity for each disk)
Backup mode	Network backup,USB hard disk, Usb burner,SATA burner
Data Export Device	USB HDD, USB Stick
NETWORK	
Client Connection	1 RJ45,10M/100M/1000M self-adaptive LAN port
Video in Connection	8ch POE Input
Remote Data Export	AVI, i8
Event Notification	Email (attach clip (.cbf) .MP4), Callback to Remote S/W Push notification (Mobile), SNS (Twitter)
Two-way audio	Yes
Client Viewer	General VMS software
POE	
Port	8ch, 10、 100Mbps Ethernet power supply ports
Output	104W
Support Standard	IEEE802.3af
GENERAL	
Operating System	Embedded Linux
System Resources	Simultaneous multi-channelreal-time recording,playback,network operation, USB backup
PTZ control	Control PTZ device by network
Approvals	FCC, CE
Power Supply	48V – 2.5A
Power Consumption	<10W(without HDD)
Working Temperature	-10°C~+55°C
Dimension	350mm(W)x240mm(D) 68mm(H)

DIMENSIONS

